

StrobeWise™

Next Generation Vehicle Safety

Ghost Single Mini Light for StrobeWise™

ESW120SBA - Black

ESW120SWA - White



Screw Mount

Drill hole with #27 (Ø.144") drill bit

Adhesive Mount

1"x1.25" Pads

INSTALLATION

LIGHT-HEAD

The light head should be center mounted (approximately along the center line of the vehicle) allowing following drivers to clearly see the light head. Light-head can be mounted inside or outside of the rear window or surface mounted to the rear body of the vehicle. Take care not to mount the light-head where human activities might jar and alter the alignment. Both light head and control module have mounting holes. Mounting hardware is provided for the light head. GHOST Single LED Mini Light has 3 installation options: Permanent Mount, Adhesive Mount with Super Duty Automotive Grade 3M Tape or Edge Mount Bracket.

For other light head options see our web site.

TECHNICAL SPECIFICATIONS

Overall Dimensions:	4.0"L x .94"H x 2.06"D
Input Voltage Range:	12Vdc
Current Consumption:	<0.5 amp
# of LEDs:	6 Generation 3 LEDs
Operating Temperature:	-40° to +65° C

OPERATION:

Connect Light module to ESWC100 or ESWC300 Primary or secondary Outputs ONLY. Connections to any other device, or operating modules independently will void warranty. (modules have no flash patterns and are not meant for Steadyon operation)

NOTE: The GHOST is a factory sealed unit that CANNOT be serviced in the field. Any attempt to gain access to the GHOST unit will most likely cause permanent damage and void its warranty.

⚠ WARNING

This product contains high intensity LED devices. To prevent eye damage, DO NOT stare into light beam at close range.