



## Universal Interior Windshield Lightbar Now available in three modules



Adjustable plate enables lightbar to fit any windshield.

Split, Two-piece

ENFWBFS

### Features

- Modules are offered in single color 6 or 9 LEDs, dual color 12 LEDs or tricolor 18 LEDs
- Windows-based PC application simplifies programming and enhances configurability and control
- User configurable options include cruise mode, nighttime manual dimming, 34 programmable flash patterns and steady burn
- Direct connect option is available with single or dual color lightbars
  - The lightbar simplifies installation by eliminating the breakout box and connecting activation wires directly to the lightbar
- Takedown modules can be designated anywhere (interior windshield)
- Universal model with adjustable mounting brackets accommodate most windshield angles for even broader vehicle compatibility

**INPUT VOLTAGE RANGE** 10-16 Vdc

**NUMBER OF LEDS AND MAXIMUM CURRENT DRAW @ 12.8 VDC**

**LED Modules** 6 LED Single Color: <1.0 Amp; 9 LED Single Color: <1.5 Amps; 12 LED Dual Color: <1.0 Amp or 18 Tricolor: <1.0 Amp

**NUMBER OF LEDS AND MAXIMUM WATTAGE @ 12.8 VDC**

**Inboard Warning Modules** 6 LED Single Color: <6.4 Watts; 9 LED Single Color: <9.6 Watts; 12 LED Color: <6.4 Watts or 18 LED Tricolor: <6.4 Watts

**Takedown** 6 LED: <12.8 Watts (interior windshield)

**Work Light** 6 LED: <12.8 Watts (interior rear deck)

**FLASH PATTERNS**

**Warning** 34

**Arrow L/C/R** 8

**OPERATING TEMPERATURE** -40° C to +65° C / -40° F to +149° F

**DIMENSIONS**

**Length** 14.3" (36 cm) each side

**Height** 1" (2.5 cm)

**Depth** 5" to 7.5" (12.7 cm to 19 cm) each side is adjustable

**WARRANTY** Five-year

Contact your sales representative for additional information.

PO Box 206 / 3900 Central Parkway  
Hudsonville, MI 49426

800.338.7337 / 616.896.7100  
Fax 616.896.1226 / Order fax 616.896.1286